



LED EcoMax DC 12V Strip


Features

- Broad beam angle
- High quality
- Energy efficient

Benefits

- Simple and safe installation
- Durable for Indoor use

Application



Specification

Product Description	Power (W/m)	Lumen (lm/m)	Beam Angle (°)	CCT (K)	Lifetime (hrs)	Energy Level
LED E 12/2835 6W/60 Bare 5M	6	580	120	2400	15000	A+
LED E 12/2835 6W/60 Bare 5M	6	620	120	2700	15000	A+
LED E 12/2835 6W/60 Bare 5M	6	650	120	3000	15000	A+
LED E 12/2835 6W/60 Bare 5M	6	680	120	4000	15000	A+
LED E 12/2835 6W/60 Bare 5M	6	690	120	6500	15000	A+
LED E 12/2835 6W/60 Tube 5M	6	550	120	2400	15000	A+
LED E 12/2835 6W/60 Tube 5M	6	590	120	2700	15000	A+
LED E 12/2835 6W/60 Tube 5M	6	620	120	3000	15000	A+
LED E 12/2835 6W/60 Tube 5M	6	650	120	4000	15000	A+
LED E 12/2835 6W/60 Tube 5M	6	660	120	6500	15000	A+
LED LV STRIP 12V U 4W BL+DRIVER	4	500	120	3000	15000	A+
LED LV STRIP 12V U 4W BL+DRIVER	4	500	120	6500	15000	A+
LED LV STRIP 12V U 12W	12	1200	120	3000	15000	A+
LED LV STRIP 12V U 12W	12	1200	120	6500	15000	A+

Application Conditions


IP	20
Operating Temperature	-10-45°C
Application Temperature	25°C
Storage Environment	-25-50°C

Electrical Supply

Frequency (Hz)	50/ 60
Voltage (V)	12
AC/DC	DC

Mechanical Properties


Optical Material	PVC
Housing Material	Copper
Finishing Colour	White



Packaging Information

Item Description	Single Box(1pc/box)		Packaging Unit			Remark
	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Dimensions(mm) (LxWxH)	Gross Weight (kg)	Packing Qty (pcs/unit)	
LED E 12/2835 6W/60 Bare 5M	5000*8*2.5	0.06	460*230*380	8	80	4*20 roll (5M/roll)
LED E 12/2835 6W/60 Tube 5M	5000*10*4	0.21	465*305*270	10.4	40	2*20 roll (5M/roll)
LED LV STRIP 12V U 4W BL+DRIVER	5000*8*1.3	0.26	445*370*230	5.6	20	5M strip and driver
LED LV STRIP 12V U 12W	5000*8*1.3	0.08	460*230*390	7.2	80	only 5M strip
LED E 12/2835 Input connector	/	0.002	285*220*245	24	100	120*100pcs
LED E 12/2835 Middle connector	/	0.001	285*220*245	32	100	320*100pcs
LED E 12/2835 Jumper connector	/	0.003	285*220*245	18	100	60*100pcs
LED E Strip Driver 30W DC12V	194*43*43	0.208	250*225*170	4.76	20	20pcs
LED E Strip Driver 60W DC12V	194*43*43	0.264	250*225*170	6	20	20pcs

Dimensional Drawing



	6W(Tube)	6W(Bare)	4/12W
A (mm)	5000	5000	5000
B (mm)	10	8	8
C (mm)	4	2.5	1.3