



LED Spot Lamp E3



Up to 110lm/W



CRI>80



No Blue Light



Flicker Free

Application



Shopping Mall



Restaurant



Hotel



Home

Specification

Item Code	Item Description	Power (W)	CCT (K)	Input Voltage	Lumen (lm)	Efficacy (lm/W)	Beam Angle (°)	Average Lifetime (hrs)	CRI
800021000500	LED-E3-GU10-5W-36D-2700K-CT	5	2700	220-240	550	110	36°	20000	80
800021000600	LED-E3-GU10-5W-36D-4000K-CT	5	4000	220-240	550	110	36°	20000	80
800021000700	LED-E3-GU10-8W-36D-2700K-CT	8	2700	220-240	880	110	36°	20000	80
800021000800	LED-E3-GU10-8W-36D-4000K-CT	8	4000	220-240	880	110	36°	20000	80
800021000100	LED-E3-MR16-5W-36D-2700K-CT	5	2700	12V A/DC	550	110	36°	20000	80
800021000200	LED-E3-MR16-5W-36D-4000K-CT	5	4000	12V A/DC	550	110	36°	20000	80
800021000300	LED-E3-MR16-8W-36D-2700K-CT	8	2700	12V A/DC	880	110	36°	20000	80
800021000400	LED-E3-MR16-8W-36D-4000K-CT	8	4000	12V A/DC	880	110	36°	20000	80
800021001300	LED-E3-GX5.3-5W-36D-2700K-CT	5	2700	220-240	550	110	36°	20000	80
800021001400	LED-E3-GX5.3-5W-36D-4000K-CT	5	4000	220-240	550	110	36°	20000	80
800021001500	LED-E3-GX5.3-8W-36D-2700K-CT	8	2700	220-240	880	110	36°	20000	80
800021001600	LED-E3-GX5.3-8W-36D-4000K-CT	8	4000	220-240	880	110	36°	20000	80
800021000900	LED-E3-GU10-5W-Dim-36D-2700K-CT	5	2700	220-240	550	110	36°	20000	80
800021001000	LED-E3-GU10-5W-Dim-36D-4000K-CT	5	4000	220-240	550	110	36°	20000	80
800021001100	LED-E3-GU10-8W-Dim-36D-2700K-CT	8	2700	220-240	880	110	36°	20000	80
800021001200	LED-E3-GU10-8W-Dim-36D-4000K-CT	8	4000	220-240	880	110	36°	20000	80
800021001700	LED-E3-GX5.3-8W-Dim-36D-2700K-CT	8	2700	220-240	880	110	36°	20000	80
800021001800	LED-E3-GX5.3-8W-Dim-36D-4000K-CT	8	4000	220-240	880	110	36°	20000	80

Electrical Supply	
Frequency (Hz)	50/60
Voltage (V)	12V A/DC or 220-240V
AC / DC	AC or DC


Mechanical and Finishing Properties	
Housing Material	Plastic+Aluminum
Optical Material	PC
Finishing Color	White

Application Conditions	
IP	IP20
Operating Temperature	-20 ~ +40 °C
Application Temperature	25 °C
Storage Environment	-25-+50 °C

Packaging Information

Item		Single box(1pc/box)		Outer box		
Item Code	Item Description	Dimensions(mm) (LxWxH)	Gross Weight (g)	Dimensions(mm) (LxWxH)	Gross Weight (g)	Packing Qty (pcs/CTN)
800021000500	LED-E3-GU10-5W-36D-2700K-CT	50*50*55	39.9	520*265*130	4300	100
800021000600	LED-E3-GU10-5W-36D-4000K-CT	50*50*55	39.9	520*265*130	4300	100
800021000700	LED-E3-GU10-8W-36D-2700K-CT	50*50*55	39.9	520*265*130	4300	100
800021000800	LED-E3-GU10-8W-36D-4000K-CT	50*50*55	39.9	520*265*130	4300	100
800021000100	LED-E3-MR16-5W-36D-2700K-CT	50*50*50	37.5	520*265*120	4060	100
800021000200	LED-E3-MR16-5W-36D-4000K-CT	50*50*50	37.5	520*265*120	4060	100
800021000300	LED-E3-MR16-8W-36D-2700K-CT	50*50*50	37.5	520*265*120	4060	100
800021000400	LED-E3-MR16-8W-36D-4000K-CT	50*50*50	37.5	520*265*120	4060	100
800021001300	LED-E3-GX5.3-5W-36D-2700K-CT	50*50*55	41.7	520*265*130	4480	100
800021001400	LED-E3-GX5.3-5W-36D-4000K-CT	50*50*55	41.7	520*265*130	4480	100
800021001500	LED-E3-GX5.3-8W-36D-2700K-CT	50*50*55	41.7	520*265*130	4480	100
800021001600	LED-E3-GX5.3-8W-36D-4000K-CT	50*50*55	41.7	520*265*130	4480	100
800021000900	LED-E3-GU10-5W-Dim-36D-2700K-CT	50*50*55	39.9	520*265*130	4300	100
800021001000	LED-E3-GU10-5W-Dim-36D-4000K-CT	50*50*55	39.9	520*265*130	4300	100
800021001100	LED-E3-GU10-8W-Dim-36D-2700K-CT	50*50*55	39.9	520*265*130	4300	100
800021001200	LED-E3-GU10-8W-Dim-36D-4000K-CT	50*50*55	39.9	520*265*130	4300	100
800021001700	LED-E3-GX5.3-8W-Dim-36D-2700K-CT	50*50*55	41.7	520*265*130	4480	100
800021001800	LED-E3-GX5.3-8W-Dim-36D-4000K-CT	50*50*55	41.7	520*265*130	4480	100

Dimensional Drawing



Type	MR16 5W/8W	GU10 5W/8W	GX5.3 5W/8W
A	50	50	50
B	47	53	53

OPPLE SHANGHAI OFFICE

Building V3, The Mixc, 1799 Wuzhong Road,
Minhang District, Shanghai, China
ZIP: 201103

T + 86 21 3855 0000

E intersales@opple.com

WWW.OPPLE.COM/EN